

LED Round Slim Panel



MODEL SPECIFICATION

MODEL:	SIZE	WATTAGE	5CCT	LUMENS
SZ-DL9W4-SP-R-CCT-277V	4inch	9W	2700K	620-710Lm
			3000K	
			3500K	
			4000K	
			5000K	
MODEL:	SIZE	WATTAGE	5CCT	LUMENS
SZ-DL12W6-SP-R-CCT-277V	6inch	12W	2700K	960-1030Lm
			3000K	
			3500K	
			4000K	
			5000K	

DESCRIPTION

Ultra slim design, lamp thickness only 1.22".

Features color tunable technology lets the user choose between 2700K, 3000K, 3500K, 4000K, or 5000K

Wet-location rated, ideal for bathrooms, laundry, porches and garage work rooms.

Available size: 4", 6"

TECHNICAL SPECIFICATION

VOLTAGE	120-277V
POWER FREQUENCY	60Hz
POWER FACTOR	>0.9
5CCT	2700K 3000K 3500K 4000K 5000K
CRI	90
BEAM ANGLE	100°
MATERIAL	PS+AL
LIFESPAN	≥ 50,000hours
OPERATING TEMP	(-4°F~ 113°F) -20~45°C
DIMMABLE	0-10V Dimming
RATING	Suitable for Wet Locations
WARRANTY	5 year limited

LISTING

ETL Listed

FEATURES

- Baffle trim design
- Edge-lit technology, with no glare or dark spots
- Continuous dimming from 100% to 10% with many 0-10v Dimmers
- Instant on
- No flicker

INSTALLATION

No existing recessed housing or junction box required.

Suitable for most new constructions.

Install J-Box in ceiling beam, and insert light right into drywall opening.

DIMMING

Compatible with most 0-10V dimmers to give user a smooth dimming to choose the desired brightness.

Please check the recommended dimmer list in next page.

ELECTRICAL

This fixture is built with the highest quality 120-277V drivers, ensuring energy efficiency.

ENERGY SAVINGS







80% more energy savings than halogen lamps.

LED Round Slim Panel

4inch & 6inch: Easily flip the switch for desired CCT **Products view**



SIZE & DIMENSION & HOLE CUTOUT

Size	Dimension	Hole Cutout
4inch		 
6inch		 

RECOMMENDED DIMMER

LUTRON				LEGRAND
RMJS-8T-DV-B	Diva DVSTV	MS-Z101-WH	DVSTV-WH	RH4FBL3PW


ACCESSORIES



J-Box driver



Connector



Hole cutout card