

LED OUTDOOR REMOTE HEADS

ILLUMINATION

- Long lasting, efficient ultra-bright white LED lamp heads.
- High-performance chrome-plated metalized reflector and plastic lens (indoor applications) or glass lens (outdoor applications) for optimal light distribution.
- Adjustable LED lamp heads increases center-to-center spacing with 12 LEDs in each lamp head.

ELECTRICAL

- Powered from low voltage power source with low voltage wiring (not provided).

MOUNTING

- Universal mounting base mounts to single-gang switch box.
- Distance of maximum run is determined by system voltage, wire gauge and total maximum wattage on the run.
- Suitable for wall or ceiling mount.

WARRANTY/LISTING

- Three year warranty.
- UL listed.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.

HOUSING

- Indoor application remote heads are injection-molded, engineering-grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.
- Outdoor application remote heads are die-cast aluminum, sealed and gasketed in gray or black finish.

DIMENSIONS



ORDERING INFORMATION

| MODEL | OPTIONS | | HOUSING | | VOLTAGE | COLOR | LAMP TYPE |
|-----------------------|---------|---|---------|----------|---|-------|--------------|
| SZ-EXIT-Remote (IP65) | (blank) | For Standard Non-Self-Diagnostic Fixtures | A | Die-Cast | For Use With 3.6V, 9.6V, 12V & 3.6-9.6V DC Power Source | Gray | 12 LEDs 1.5W |
| | SDT | For Use With Fixtures With A Self-Diagnostic Option | | | | | |